



Indorama Ventures Fibers Germany GmbH

Trademark Service

Max-Fischer-Str. 11

86399 Bobingen, Germany

trademarkservice.IVFG@de.indorama.net

Tel. +49 8234 9688 1673

www.indoramaventures.com



Approval of the Trademark Trevira CS®

PUGI R. G. S.r.l.
Via Garibaldi 33 b
51037 Montale (PT)
Italy

Application No.:	230743.2
Date of issue:	01.04.2026
Valid until:	26.09.2028
Article name:	NEMI L
Color:	black
End use:	Drapes Curtains Upholstery fabrics Wall coverings Transport sector
Square weight (g/m²):	240
According to customer specification	
Composition of the raw materials:	100% Polyester
Composition of the fabric:	100% Trevira CS

The tested article NEMI L with application no. 230743 is granted approval for the trademark Trevira CS® for interior use.

This article was tested according to DIN 4102 part 1, 6.2 and thus also meets the requirements for fire class DIN 4102-B1.

The article was tested according to the French Standard NF P 92-504 (Propagation de flamme) and thus also meets the requirements for class M1 according to NF P 92-503, 92-505 and 92-507.

The article meets the requirements for class 1 according to EN 13773.

DIN EN ISO 6940/6941: For Trevira CS fabrics no ignition and no rate of flame spread is measured.

The article can also meet the requirements for the fire index BKZ 5.3 (BKZ = fire index, combustibility 5 = flame retardant, level of smoke emission 3 = low smoke emission) according to the Swiss standard SN 198898.

INDORAMA
VENTURES

Indispensable Chemistry



The article meets also the requirements according to British Standard BS 5867 part 2 type C.

The article meets also the requirements according to British Standard BS 5852: ignition source 0 (cigarette), ignition source 1 (small gas flame) and ignition source 5 (crib 5) in conjunction with suitable combustion modified foams (at least 50 kg/m³).

The article can meet the requirements of class 1Y according to BS 476: Part 7: 1997 / Surface Spread of Flame.

The article also meets the requirements according to the North American NFPA Life Safety Code 101, class A, Test Standard ASTM E84 Surface Burning Characteristics, Test Report No. 12-002-527, dated August 30, 2012.

The article can also meet the requirements according to FAR/JAR/CS 25.853 App. F to part 25, part I, § (a), (1) (ii) (vertical test, ignition time 12 sec).

Indorama Ventures Fibers Germany GmbH

(This document is valid without signature.)

