

Application for approval of the trademark TREVIRA®

Trevira GmbH
Markenprüfung /
Trademark Testing
Technikum, Gebäude 515
Max-Fischer-Straße 11
D-86389 Bobingen

Applicant

Company PUGI RG SRL
Road G.GARIBALDI 33/B
Post Code/City 51037 MONTALE PT
Country ITALY

Name / Signature 16.3.2018

Trademark Trevira CS

Article NEMI L - TRADEMARK 160476

End Use
Drapes
Transportation sector
Wall coverings

Other uses
M1,DIN 4102 PART 1 B1 BS 5867
PART2 TYPE C ,CLASS A,ASTM E84
EN 13501 CLASS B-S1,d0,SN
198898,UNI EN ISO 6940:2000 EN
1021-1+2,BS 5852 CRIB 5,NFPA
701:2010#1,EN13773,CAL117:2013,FAR
25853,NFPA 101 CON ASTM E84

Composition 100% TREVIRA CS

Fabric weight (g/sm) 240

Approval: 14.04.2016 (This Trademark approval is valid for a period of 5 years from the date of issue).
The tested article NEMI L with application no. 160476 is granted approval for the trademark Trevira CS for the interior use. It was tested according to DIN 4102 part 1, 6.2 and thus also meets the requirements for fire class DIN 4102-B1, the requirements according to British Standard BS 5867 part 2 type C, the requirements according to the North American NFPA Life Safety Code 101, class A, Test Standard ASTM E84 Surface Burning Characteristics, Test Report No. 12-002-527, dated August 30, 2012. This article qualifies for class B-s1, d0 according to the European Standard EN 13501-1. Trevira CS has been approved by the DIBt with the General Building Inspectorate Approval, Approval No. Z-56.25-3573 dd. 2 May 2013. This article can also meet the requirements for the fire index BKZ 5.3 (BKZ = fire index, combustibility 5 = flame retardant, level of smoke emission 3 = low smoke emission) according to the Swiss standard SN 198898. DIN EN ISO 6940/6941: For Trevira CS fabrics no ignition and no rate of flame spread is measured. This article meets the requirements according to EN 1021 part 1+2 in conjunction with polyurethan foams with a density of more than 30 kg/m³. It also meets the requirements according to British Standard BS 5852: ignition source 0 (cigarette), ignition source 1 (match) and ignition source 5 (crib 5) in conjunction with suitable combustion modified foams (at least 50 kg/m³). This article also meets the requirements according to the North American standard NFPA 701: 2010 Test Method #1 (based on the Test Reports Govmark, New York No. 2-94779, 2-94780, 2-94781). The article meets the requirements for class 1 according to EN 13773. This article can meet the requirements according to California TB 117, section 1 - cover fabric and the requirements according to FAR/JAR/CS 25.853 App. F to part 25, part I, § (a), (1) (ii) (vertical test, ignition time 12 sec).

W.G. W.K. i.A. J. Riedl - May

Trevira GmbH, Trademark Service