







# ombra - M



## Technical specifications

Test description	Norm	U.o.M.	Values and tolerances
Composition	Direttive CE	%	100% PL FR
Piece length and width		lmt.	35 ± 5 3,35 ± 5
Weight	UNI EN 12127	gr./m <sup>2</sup> -gr./mtl.	120 ± 10% / 400 ± 10%
Colour Fastness crocking dry	EN ISO 105X12	degree 1-5	4 ± 1
Lightfastness (Xenotest)	EN ISO 105 B02 Scala dei blu	degree 1-8	5 ± 1
Symbols Maintenance	UNI 8423	    	

**Acoustics/Sound absorption:** Report on acoustical charact.of materials accord. to UNI EN ISO 10534-2

**Certification:** Classe 1 Curtains, Draperies

Azimut

MED/3.19 MED/3.21: Draperies, Curtais and Bedding comp.

MED/3.18a: Surface Materials

Test report, certificates and witness of the tested material are kept in the archives of Pugi.rg Srl.  
The material object of the test was taken by sample from our. normal production.



Pugi.rg srl - 51037 Montale PT via Garibaldi, 33b - Italy  
Tel: +39.0573.557701 Fax: +39.0573.557705  
E-mail: info@pugirg.it www.pugirg.it

 made in Italy

Rev.2-07/20